

SOLVENT FREE EPOXY COATING(HOT APPLY)

Product information

- 1- Excellent mechanical strength
- 2- Excellent resistance to abrasion
- 3- Excellent resistance to chemical material and water
- 4- Excellent resistance to oil

Physical data

Colour:	customer request (white-green)
Finish:	Semigloss-gloss
Flash point:	
Resin:	24 [°] c
Cure:	24 [°] c
Volume solids:	95 ±3%
D.f.t:	400 - 450 microns
Specific gravity(mixed):	1.5 ±0.08 gr/cm ³
Theoretical coverage:	2.37 m ² /lit (at 400μ d.f.t)
Drying time at 25 [°] c:	
Touch dry:	6 hrs
Dry to handle:	24 hrs
Full cure:	7days
Component:	2
Pot life at 60 [°] c:	5-10 minutes
Mixing ratio (by volume):	
Resin:	refer to label of can
Cure:	refer to label of can
Application methods:	hot airless
Recommended cleaner:	FARCO CLEAN 13
Shelf life:	12 months when stored indoors in unopened Original containers at 25 [°] c (cool and dry Place).
Curing mechanism:	reaction between components
Substrate:	steel , welding area ,concrete

* : For recoating the surface should be free of dust ,grease and contamination